




BEARING CORP. OF AMERICAN LTD.



2.953 Inch | 75 Millimeter x 5.118 Inch | 130
Millimeter x 0.984 Inch | 25 Millimeter SKF NU
215 ECP/C3 Cylindrical Roller Bearings

Bearing No. NU 215 ECP/C3

NU 215 ECP/C3 Bearing 2D drawings and 3D CAD
models

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	1.301
Product Group	B04144
Bore Profile	Straight
Cage Material	Polymer
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	75MM Bore; Straight Bore Profile; 130MM Outside Diameter; 25MM Width; Polymer Cage Material; RBEC 1 ISO P0; Single



BEARING CORP.OF AMERICAN LTD.

	Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C3-Loose Int
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	NU 215 ECP/C3
Weight / LBS	2.866
d	2.953 Inch 75 Millimeter
D	5.118 Inch 130 Millimeter
B	0.984 Inch 25 Millimeter
bore diameter:	75 mm
precision rating:	RBEC 1 (ISO Class Normal)
outside diameter:	130 mm
maximum rpm:	6000 RPM
overall width:	25 mm
bearing material:	Steel
flanges:	(2) Outer Ring
cage material:	Polyamide
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
internal clearance:	C3
application:	Piston Type Machines, Rolling Mills, Spindles/Machine Tools
ring separation:	Separable Ring
outer ring width:	25 mm
operating temperature	Maximum of +300 ° F



BEARING CORP.OF AMERICAN LTD.

range:	
fillet radius:	1.5 mm
dynamic load capacity:	150 kN
series:	NU2
static load capacity:	156 kN